



HGS (INDIA) LIMITED



428XL WPSR DSU 1-4 LINK CABLE



158, Sector-4, IMT Manesar, Gurugram-122050 Haryana INDIA
Tel: +91 (0124) 4681800, Fax: +91 (0124) 4681845
Email: sales@hgsindia.com




HGS (INDIA) LIMITED



SCHEMATIC

428XL WPSR DSU 1-4 LINK CABLE



3	4 CONDUCTOR FSC LINE CABLE WPSR, ORANGE	As Req.
2	428 DSU3 WPSR TAKE OUT ASSY.	04 Nos
1	4 PIN WPSR END CONNECTOR ASSY.	02 Nos.
S. NO.	DESCRIPTION	QTY



HGS (INDIA) LIMITED



SPECIFICATIONS

428XL WPSR DSU 1-4 LINK CABLE

Parameters	Value
Field Conditions	Wet
Conductor Arrangement	1 quad
Conductor Type	Stranded
Water Blocked	Yes
Maximum Water Depth	15 M
Diameter	9.5 mm
Tensile Strength (Nude Cable)	>300 daN
Tensile Strength (with Connector)	>250 daN
Stress Member	Aramid Braid/Kevlar
Weight	95 Kg/Km
Double Jacket	Water proof double jacket
Operating Temperature	-40 °C to 70 °C (standard cable); -45 °C to 70 °C (cold weather cable)
Storage Temperature	-40 °C to 85 °C (standard cable); -55 °C to 85 °C (cold weather cable)
Data Transfer Rate	16 Mbps
Compatibility:	
WPSR cables are compatible with Digital Sensor Units (DSU-3), 428XL LAUL & 428XL LAUX	

Version 1.2